



S01 1U Black Sliding Patch Panel - 24 Position ST/FC up to 24 fibres



This innovative, robust 1U sliding patch panel. This panel has been designed to accept up to 24 fibres housed within a 1U space.

With the ability to use a full array of Adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 4 standard cable entry points for, loose tube, tight buffer, pre terminated and steel tape armoured cable.

Each panels has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.

FEATURES

- Up to 24 fibres in 1U
- Multiple Adaptor options available
- 24 Adaptor positions
- Individually labelled ports
- 45° open working angle
- Accepts loose tube, distribution and pre terminated cables
- RoHS, REACH SvHC and UL rated
- Fits standard 19"

APPLICATIONS

- Data centres, premise installations, telecommunication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- Data communication
- Indoor applications

SPECIFICATION

ELEMENT	CHARACTERISTIC
U Size	1U (44.4mm)
Width	482mm
Depth	205mm
Net weight	2.5 kgs
Packaged weight	3 kgs
Packaged dimensions	450mm W X 55mm H x 260mm D
IP rating	IP20
Suitable for Adaptor type	ST/ FC
Number of ports	24
Cable Entry 20mm	2
Cable entry 25mm	2
Mounting Adjustment range	50mm
Material	Cold- rolled steel
Material thickness	1.2mm
Material coating	Powder coating

ELEMENT	CHARACTERISTIC
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC

ORDERING INFORMATION

LOADED WITH PIGTAILS

		OS1/OS2	OM1	OM2	OM3	OM4
	PART NUMBER	9/125	62.5/125	50/125	50/125	50/125
		Singlemode	Multimode	Multimode	Multimode	Multimode
ST Singlemode	S01STS24/Z	P1	-	-	-	-
ST Multimode	S01STM24/Z	-	P2	P3	P4	P5
FC Singlemode	S01FCS24/Z	P1	-	-	-	-
FC Multimode	S01FCM24/Z	-	P2	P3	P4	P5
FC APC Singlemode	S01FCA24/Z	P1	-	-	-	-

EXAMPLE PART NUMBERS


Loaded with ST Singlemode Adaptors: **S01STS24/Z**

Loaded with ST Singlemode Adaptors and OS1/OS2 Singlemode Pigtails: **S01STS24P1/Z**

Also available in Grey, please contact sales for more information.

Please contact our sales team on +44 (0) 1908 441 121 for further ordering information.

TECHNICAL DRAWING



CONTACT OUR SALES TEAM TODAY

Europe: +44 1908 441 100 | sales@optronicsnet.com

Americas: +1 410 242 9026 | sales@optronicsnet.com

Asia Pacific: +86 755 2531 3694 | apac@optronicsnet.com

Middle East & Africa: +971 4 443 1028 | mea@optronicsnet.com

Web: www.optronicsnet.com